

UHF RFID MICRO TAG

- Product Specifications -



- **Model:** RS-RMT06
- **Material:** PCB
- **Frequency:** UHF 860-940MHz
- **Size:** 10×3×2.5mm, 10×5×2.5mm
- **Chip:** NXP UCODE 9
- **Protocol:** EPC Class1 Gen2; ISO18000-6C
- **Reading Range:** 10-80cm (based on reader/writer and installation method)
- **Read/Write Times:** ≥100,000 times
- **Operating Temperature:** -40°C~85°C

Product Description

Micro UHF tags consists of industrial-grade, specialized UHF tags. They feature high-temperature resistance, corrosion resistance, and an IP67 waterproof rating, while also being metal-tolerant and liquid-friendly. These tags can be paired with external RF booster antennas or directly affixed to the surfaces of metal objects, liquid containers, or assets.

Technical Parameters

Physical Characteristics	
Material	PCB
Size	10×3×2.5mm, 10×5×2.5mm
Color	Black
Operating Temperature	-40°C~85°C
Storage Temperature	-40~120°C (-40~248°F), 50% RH
Temperature Resistance	-196°C (>2000 h), 125°C (>1000 h), 260°C (5 min)
Electrical Characteristics	
Frequency	860-940MHz
Chip Type	NXP UCODE 9
Memory	EPC 128 bits (96bits), User 32 bits (64bits), TID 48 bits
Read/Write Times	≥100,000 times
Data Storage	10 years
Reading Distance	10–80 cm (depending on the tool and the depth of insertion into the slot; based on the example of being embedded in a metal surface with no metal obstruction)
*The final read range depends on RFID Reading equipment and application environment.	

★ Key Features

- Ultra-compact and metal-resistant;
- High-temperature resistant;
- Corrosion-resistant;
- IP67 Waterproof.

🔧 Application

Metal tool management, medical surgical tool management, etc.



📊 Performance

Chip: NXP UCODE 9
Frequency: 860-940MHz

CONTACT

Ms. Edith Chen

P/W: +86 13612933572

Email: info@rfid silicone.com

Skype: live:cxjrfid

ADD: 4th Floor, Building B, Phase 1, Longzhixiang
Tiancheng Sci-Tech Park, No.27-5 Tiancheng Road,
Longhua District, Shenzhen, China 518100

